

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Pearl Grey Nature Grading matt lacquer  
4-sided mini bevel

1699816





---

Oak Pearl Grey  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699816 "Pearl Grey"                                                                                        |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Golden Oak lightly smoked Nature Grading matt lacquer  
4-sided mini bevel

1699835





---

Golden Oak lightly smoked  
Nature Grading matt lacquer

Loft-160

---

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699835 "Golden Oak lightly smoked"                                                                         |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Astoria Nature Grading matt lacquer  
4-sided mini bevel

1699833





---

Oak Astoria  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699833 "Astoria"                                                                                           |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Carvi Monde Nature Grading matt lacquer  
4-sided mini bevel

1699761





---

Oak Carvi Monde  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699761 "Carvi Monde"                                                                                       |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Cognac Matte Nature Grading matt lacquer  
4-sided mini bevel

1699834





---

Oak Cognac Matte  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699834 "Cognac Matte"                                                                                      |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Cordovan Nature Grading matt lacquer  
4-sided mini bevel

1699819





---

Oak Cordovan  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699819 "Cordovan"                                                                                          |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical -<br>Impact noise reduction                                                                                          | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Metropolitan smoked Nature Grading matt lacquer  
4-sided mini bevel

1699832





---

Oak Metropolitan smoked  
Nature Grading matt lacquer

Loft-160

---

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699832 "Metropolitan smoked"                                                                               |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical -<br>Impact noise reduction                                                                                          | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Oblivion Nature Grading matt lacquer  
4-sided mini bevel

1699831





---

Oak Oblivion  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699831 "Oblivion"                                                                                          |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Perlmutter Matte Nature Grading matt lacquer  
4-sided mini bevel

1699817





---

Oak Perlmutter Matte  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699817 "Perlmutter Matte"                                                                                  |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical -<br>Impact noise reduction                                                                                          | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Pure Loft Nature Grading matt lacquer  
4-sided mini bevel

1699820





---

Oak Pure Loft  
Nature Grading matt lacquer

Loft-160

---

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699820 "Pure Loft"                                                                                         |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical -<br>Impact noise reduction                                                                                          | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |

# PARADOR

## Engineered wood flooring Loft-160

wide plank look  
2010 × 160 × 13 mm

Oak Silk Loft Nature Grading matt lacquer  
4-sided mini bevel

1699818





---

Oak Silk Loft  
Nature Grading matt lacquer

---

Loft-160

# Engineered wood flooring

## Loft-160

### Product details

|                   |                                                                                                             |
|-------------------|-------------------------------------------------------------------------------------------------------------|
| Product           | 1699818 "Silk Loft"                                                                                         |
| Wood type         | Oak                                                                                                         |
| Format            | 2010 × 160 × 13.0 mm                                                                                        |
| Number of layers  | 3                                                                                                           |
| Packaging         | Pack: 9 elements / 2.894 m <sup>2</sup> / 21.375 kg<br>Pallet: 32 packs / 92.621 m <sup>2</sup> / 684.00 kg |
| Guarantee         | Residential: 25 years<br>Commercial: 5 years                                                                |
| Notes             | Cleaning and maintenance see instructions<br>Technical changes reserved                                     |
| Surface finishing | Bona Performance Lacquer                                                                                    |

### Further product details

|                     |                                             |
|---------------------|---------------------------------------------|
| Installation method | Floating installation or all-over adhesion. |
| Connection          | Click system                                |

### Tolerances (EN 13489)

|                                                          |                |
|----------------------------------------------------------|----------------|
| Admissible difference in length ( $\pm 0.1$ %)           | $\pm 0.05$ %   |
| Admissible difference in width ( $\pm 0.2$ mm)           | $\pm 0.1$ mm   |
| Squareness of the element ( $\leq 0.1$ %)                | $\leq 0.05$ %  |
| Longitudinal curvature along the element ( $\leq 0.1$ %) | $\leq 0.05$ %  |
| Transverse curvature across the width ( $\leq 0.1$ %)    | $\leq 0.08$ %  |
| Height differences of elements ( $\leq 0.2$ mm)          | $\leq 0.18$ mm |
| Moisture content at the time of first delivery (5-9%)    | 6 – 8 %        |
| Top layer                                                | $\pm 3.6$ mm   |
| Special treatment / finishing                            | natural matt   |

### Classification

|                                                                                                                                                                                                                     | Test standard | Rating                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------------------------------------------------|
|  Resistance to roller castor chairs                                                                                              | EN 425        | We recommend the use of a conventional chair mat |
|  Effect of a furniture leg                                                                                                       | EN 424        | No visible changes                               |
|  Thermal resistance<br>Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier | EN 12664      | 0.087 m <sup>2</sup> *K/W (plank)                |
|  Reaction to fire<br>click installation as floated floor                                                                         | EN 13501-1    | D <sub>fl</sub> s1                               |
|  Acoustical - Impact noise reduction                                                                                             | ISO 717-2     | 18 dB (with Akustik-Protect 100)                 |
| Disposal                                                                                                                                                                                                            |               | EWC code number 20 01 38                         |